



MITSUBISHI RF POWER MODULE  
**M68702H**

150-175MHz, 12.5V, 60W, FM MOBILE RADIO



- PIN:  
 ① Pin : RF INPUT  
 ② Vcc1: 1st. DC SUPPLY  
 ③ Vcc2: 2nd. DC SUPPLY  
 ④ PO : RF OUTPUT  
 ⑤ GND: FIN

**ABSOLUTE MAXIMUM RATINGS** (Tc=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Ratings	Unit
Vcc	Supply voltage	ZG=ZL=50	17	V
Icc	Total current	ZG=ZL=50	20	A
P <sub>in</sub> (max)	Input power	f=150-175MHz, ZG=ZL=50, Vcc1 12.5V	600	mW
P <sub>O</sub> (max)	Output power	Ditto	75	W
T <sub>C</sub> (OP)	Operation case temperature	Ditto	-30 to +110	°C
T <sub>stg</sub>	Storage temperature		-40 to +110	°C







Note. Above parameters are guaranteed independently.

**ELECTRICAL CHARACTERISTICS** (Tc=25°C unless otherwise noted)

Symbol	Parameter	Test conditions	Limits		Unit
			Min	Max	
f	Frequency range	Vcc1=Vcc2=12.5V, P <sub>in</sub> =300mW, ZG=ZL=50	150	175	MHz
P <sub>O</sub>	Output power		60		W
η	Total efficiency		45		%
2fo	2nd. harmonic			-30	dBc
3fo	3rd. harmonic			-30	dBc
in	Input VSWR			3	-
-	Load VSWR tolerance	Vcc1=Vcc2=12.5V, P <sub>O</sub> =60W (P <sub>in</sub> :controlled), ZG=50, Load VSWR=8.8:1 (All phase)	No degradation or destroy		-





Note. Above parameters, ratings, limits and test conditions are subject to change.

**TYPICAL PERFORMANCE DATA**



MITSUBISHI RF POWER MODULE  
**M68702H**

150-175MHz, 12.5V, 60W, FM MOBILE RADIO



This datasheet has been download from:

[www.datasheetcatalog.com](http://www.datasheetcatalog.com)

Datasheets for electronics components.